PATENT ABSTRACTS OF JAPAN

(11)Publication number : 06-150929

(43)Date of publication of application : 31.05.1994

(51)Int.Cl. H01M 4/58
H01M 4/02
H01M 10/40

(21)Application number : 04-302002

(22)Date of filing : 12.11.1992

(71)Applicant : MATSUSHITA ELECTRIC IND CO LTD

(72)Inventor : OKAMURA KAZUHIRO
NITTA YOSHIAKI
HARAGUCHI KAZUNORI
KOBAYASHI SHIGEO

(54) NON-AQUEOUS ELECTROLYTE SECONDARY BATTERY

(57)Abstract:

PURPOSE: To provide a secondary battery formed by using non-aqueous electrolyte and having an excellent cycle characteristic by using composite oxide made by partially replacing Li in material represented by chemical formula LiNiO2 with at least one of Na and K, for a positive electrode active material..



CONSTITUTION: In a chemical formula LixMyO2 (wherein M is at least one of Na and K) a positive electrode including active material wherein values of x and y in the formula meet conditions of 0<x+y<=1.0 and 0<y<=0.3, a negative electrode using either of lithium, lithium alloy or carbon material into and from which lithium can be inserted and extracted respectively as an active material and non-aqueous material are used to construct a battery. By using such a positive electrode, a non-aqueous electrolyte secondary battery having good cycle time characteristic can be provided.

LEGAL STATUS

[Date of request for examination]	18.11.1997
[Date of sending the examiner's decision of rejection]	
[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]	
[Date of final disposal for application]	
[Patent number]	3049973
[Date of registration]	31.03.2000
[Number of appeal against examiner's decision of rejection]	
[Date of requesting appeal against examiner's decision of rejection]	
[Date of extinction of right]	

【図3】



【図4】



フロントページの続き

(72)発明者　小林　茂雄
大阪府門真市大字門真1006番地　松下電器
産業株式会社内

5

ば正極活物質として化学式$Li_xM_yNiO_2$（但し、MはNa，Kの少なくとも1種）において、式中のxおよびyの値が$0<x+y\leqq1.0$、かつ$0<y\leqq0.3$の条件を満たすものを用いることにより、サイクル特性に優れた非水電解液二次電池を得ることができる。

【図面の簡単な説明】

【図1】本発明の実施例における円筒形電池の縦断面図

【図2】$Li_xM_yNiO_2$（但し、MはNa，Kの少なくとも1種）で、yの値の違いによる初期放電容量の違いを示す図

【図3】$Li_xM_yNiO_2$（但し、MはNa，Kの少なくとも1種）で、yの値の違いによる充放電サイクル特

6

性の違いを示す図

【図4】$Li_xM_{0.1}NiO_2$（但し、MはNa，Kの少なくとも1種）で、Mに占めるKとNaの比率の違いによる充放電50サイクル目の放電容量の違いを示す図

【符号の説明】

1　電池ケース
2　封口板
3　絶縁パッキング
4　極板群
5　正極リード
6　負極リード
7　絶縁リング

【図1】



【図2】